

Max-Flow Series

3 POINT HITCH LEAF & DEBRIS BLOWERS



THE MOST POWERFUL BLOWER ON THE MARKET, PERIOD.

AgriMetal

Best blowers in the industry

THE MOST POWERFULL BLOWER ON THE MARKET, PERIOD



Our patent pending impeller is made of a special composite. Its exclusive design increases the airflow CFM by about 25% compared to other blowers on the market. Its lightweight construction reduces the load on the belt. Once the PTO is engaged it requires less energy at full throttle, making the MAX-FLOW debris blower the most powerful one on the market, period.

The paddles of the impeller have an opening located by the central drive shaft, allowing air to load through the center as well as from both sides of each paddle. The extra air loading from the center feed the next coming paddles, increasing performance by 25%. That's why we call it the Max-Flow (patent pending).

DETAILS



Set of air deflectors available

All 3-point hitch AgriMetal blowers are available without an air deflector. However, a hydraulic deflector kit is an available option. The kit includes two deflectors; one at 180 degrees to deflect the airflow in opposite direction, plus a downward

deflector to lift up and blow away grass clippings, aeration cores or leaves matted to the ground. Both deflectors are controlled from the operator's seat.



Banded V belt drive system

The MAX-FLOW impeller is driven by a banded V belt, equipped with an automated spring tensioner for minimum maintenance. This type of belt eliminates the risk of slipping and bouncing for a smooth and vibration free operation that will last for many years

to come, drastically reducing operation cost.



Anti-scalp roller

A 4-inch diameter anti-scalp roller is located on the back to prevent turf damage.



Caster wheels

The models B-35 and B-50-TP come standard with castor wheels for hard surface or turf clean up application.



Optional large turf roller

Another AgriMetal innovation is the optional larger roller, which the blower rides on. Thanks to this roller, the blower allows you to work in the worst fall conditions without marking or compacting the fairway. In contrast to the competition, the roller will

often repair imperfections on the fairways. Furthermore, flat tires are a thing of the past due to the use of the roller. The MAX-FLOW series of blowers is designed for maximum productivity and minimum maintenance; keeping the operator working in the field where he belongs.

Note: roller option is only available at AgriMetal authorized Golf & Turf distributors.

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment & accessories, and may not illustrate all standard equipment.

LEADER IN LEAF AND DEBRIS HANDLING EQUIPMENT

AgriMetal

www.agrimetal.com

Part number: NC 13-72-0048

1006, rue Principale
Wickham, Quebec
Canada J0C 1S0
tel.: 1-819-398-6883
1-888-398-6883
fax: 1-800-529-5311
info@agrimetal.com

Your local dealer:

Specifications

<i>Description</i>	<i>1600</i>	<i>2500</i>
Type	3 POINT HITCH	3 POINT HITCH
Number of blades	6	7
Impeller size	22" X 9" (56 CM X 23 CM)	28" X 11" (71 CM X 28 CM)
Impeller RPM	1520 TR/MN	1520 TR/MN
Flow rate	4010 CFM	6500 CFM
Air flow speed	130 MPH (210 KM)	140 MPH (225 KM)
Decibels	87	91
Outlet size	6" X 10" (15CM X 25CM)	7.5" X 12" (19 CM X 30CM)
180 degree manuel deflector	YES (STANDARD)	NO
Hydraulic deflector kit	NO	YES (OPTIONAL)
Drive system	2-5/8 V BELT	3-5/8 V BELT
PTO shaft	INCLUDED	INCLUDED
Minimum HP recommended	16 HP AT PTO	25 HP AT PTO
Length	33" (84CM)	44" (111CM)
Width	54" (137 CM)	36" (91CM)
Height	36 1/2" (93 CM)	50" (127CM)
Machine weight	310 LBS (141KG)	495 LBS (225KG)

Specifications

<i>Description</i>	<i>B-35</i>	<i>B-50</i>
Type	3 POINT HITCH	3 POINT HITCH
Number of blades	8	8
Impeller size	34" X 13" (86 CM X 33 CM)	34" X 13" (86 CM X 33 CM)
Impeller RPM	1290 TR/MN	1410 TR/MN
Flow rate	12 500 CFM	13 750 CFM
Air flow speed	180 MPH (290 KPH)	200 MPH (320 KPH)
Decibels	75	77
Outlet size	9" X 14" (23 CM X 36 CM)	9" X 14" (23 CM X 36 CM)
Hydraulic deflector kit	YES (OPTIONAL)	YES (OPTIONAL)
Drive system	(ONE PIECE) 5-5/8 V BELT	(ONE PIECE) 5-5/8 V BELT
PTO shaft	INCLUDED	INCLUDED
Minimum HP recommended	35 HP AT PTO	45 HP AT PTO
Length	41" (104 CM)	41" (104 CM)
Width	61.5" (156 CM)	61.5" (156 CM)
Height	54" (137 CM)	54" (137 CM)
Machine Weight	715 LBS (325 KG)	720 LBS (327 KG)

LEADER IN LEAF AND DEBRIS HANDLING EQUIPMENT

AgriMetal

www.agrimetal.com

1006, rue Principale
Wickham, Quebec
Canada J0C 1S0
tel.: 1-819-398-6883
1-888-398-6883
fax: 1-800-529-5311
info@agrimetal.com

Your local dealer: