


Verti-Drain® 1513

The lightweight Verti-Drain® 1513 can work to a depth of 6" / 150 mm and is well suited to sensitive turf surfaces. The belt driven machine operates a high speed while giving a neat and consistent hole pattern. An optional rear roller can be added to smooth the surface and leave a neat finish.



Specifications

SKU	111.215.013
Operation	Tractor Mounted , Self-Propelled
Working width (m)	1.32
Working width (inch)	52
Max. Working depth (mm)	150
Max. Working depth (inch)	6
Working speed at hole spacing 65 mm (km h)	2.12
Working speed at hole spacing 2 1 2 inch (mph)	1.3
Weight (kg)	425
Weight (lbs)	937
Hole distance with 12 mm tines (mm)	55
Hole distance with 1 2 x 6 inch tines (inch)	2.17
Hole spacing distance driving direction (mm)	25 - 125
Hole spacing distance driving direction (inch)	1-7.5
Max. Diameter solid tine (mm)	12 x 150
Max. Diameter solid tine (inch)	1/2 x 6
Max. Diameter hollow tine (mm)	19 x 150
Max. Diameter hollow tine (inch)	3/4 x 6
Min. Tractor HP required	25
Max. capacity with spacing 65 mm (m ² hr)	2822
Max. capacity with spacing 2 1 2 inch (ft ² hr)	30374
Three-point hitch	3-point CAT 1
Rpm Max.	540
Gearbox oil	80W90 - 0.9L
Lubricant	EP 2
Dimensions (width mm)	970
Dimensions (height mm)	780
Dimensions (length mm)	1610
Dimensions (width inch)	38.2
Dimensions (height inch)	30.7
Dimensions (length inch)	63.4
Number of rakes	500