

# FAIRWAY AERATOR

## MODEL FA 720



**PROFESSIONAL TURF CARE EQUIPMENT**

**AgriMetal**

# FAIRWAY AERATOR

**Aeration relieves compaction and helps promote good drainage. Aeration opens the soil to let air, water, and nutrients reach the roots of your turf.**

AgriMetal FA720 Fairway Aerifier is designed for heavy duty use on your biggest aeration jobs. The design is simple, and proven. 12 cast iron wheels mounted on 6 axles work independently to follow contours and penetrate compacted areas. The 6 foot working width lets you cover up to 50 acres per day.



The FA720 is your perfect choice for aerating fairways, school grounds, sports fields, and parks! The FA 720 is available in a pull type and 3 point hitch versions.

Six heads containing two wheels float independently to follow your most demanding contours. Weight trays are standard to aid penetration on compacted areas.



Wheels can be fitted with heavy wall 3/4" coring tines or rugged slicing knives if your customers demand coreless aeration. 8 tines or knives are standard per wheel with the option of doubling to 16.



The AgriMetal FA 720 features more up and down floatation than other competitive aerators. Sealed bearings mean you can work the machine instead of working to maintain it, and the powder paint process will keep your Aerator looking like new for years to come.



	SPECIFICATIONS	
	PULL TYPE	3 POINT HITCH
FRAME	ALL STEEL WELDED CONSTRUCTION 6 PAIRS OF INDIVIDUAL FLOATING ARMS HOLD 2 75# CAST IRON WHEELS EACH.	ALL STEEL WELDED CONSTRUCTION 6 PAIRS OF INDIVIDUAL FLOATING ARMS HOLD 2 75# CAST IRON WHEELS EACH.
CAST WHEELS	HOLD 8 OR 16 TINES EACH AND HAVE SEALED BALL BEARINGS	HOLD 8 OR 16 TINES EACH AND HAVE SEALED BALL BEARINGS
MACHINE LENGTH	28" ( 71 CM )	38" ( CM )
MACHINE WIDTH	95" ( 241 CM )	80" ( CM )
MACHINE HEIGHT	38" ( 96,5 CM )	30" ( 96,5 CM )
MACHINE WEIGHT	1625 LBS ( 737 KG )	1456 LBS ( 678KG )
AERATING WHEELS	12 CAST IRON WITH SEALED BEARINGS; AERATING WHELL AXLE ( 1" ).	12 CAST IRON WITH SEALED BEARINGS; AERATING WHELL AXLE ( 1" ).
TINES	CHOICE OF 3/4" CLOSES SPOONS OR 6" SLICING KNIVES.	CHOICE OF 3/4" CLOSES SPOONS OR 6" SLICING KNIVES.
HITCH	DROP PIN TOW-TYPE HYDRAULIC LIFT CYLINDER STANDARD, OPTIONAL HAND PUMP FOR TRACTORS WITHOUT HYDRAULICS.	3 POINT HITCH
TRACTOR REQUIREMENTS	30 HP AND MORE	35 HP
OPERATING SPEED	UP TO 10 MPH ( 1- 6 KM )	UP TO 10 MPH (1- 6 KM)
TRANSPORT SPEED	UP 25 MPH	UP 25 MPH
8 TINES PER WHEEL ( 96 TOTAL )	STANDARD	STANDARD
16 TINES PER WHEEL ( 192 TOTAL )	OPTIONAL	OPTIONAL
8 OR 16 SLICING KNIVES ( 92 OR 192 )	OPTIONAL	OPTIONAL
CORING DEPTH	UP TO 4"	UP TO 4"
SHIPPING DIMENSION	28" X 96" X 46" ( 71 CM X 244 CM X 117CM )	28" X 96" X 46" (71 CM X 244 CM X 117CM)
SHIPPING WEIGHT	1700 LBS ( 771KG )	1560 LBS ( 710 KG )

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment & accessories, and may not illustrate all standard equipment.

## LEADER IN LEAF AND DEBRIS HANDLING EQUIPMENT

# AgriMetal

[www.agrimetal.com](http://www.agrimetal.com)

Part number: NC13-72-0046

1006, Principale  
Wickham, Quebec  
Canada, J0C 150

Tel : 1 819 398-6883

1 888 398-6883

Fax : 1 800-529-5311

service@agrimetal.com